FIBERGLASS HOT SWITCH STICKS

SWITCH STICKS

Switch Sticks use closed cell foam filled tubular fiberglass made in accordance with ASTM Standard F711. Both the standard head and the heavy duty prong disconnect are made of durable high strength aluminum bronze alloy.

ONE SECTION

Item #		Dimensions: Dia. × Length		Weight each
HD	ST	in × ft	mm × m	lb (kg)
9950-ES	9933-ES	1.25 in × 4 ft	31.7 mm × 1.2 m	2.1 lb (1 kg)
9951-ES	9934-ES	1.25 in × 6 ft	31.7 mm × 1.8 m	2.9 lb (1.3 kg)
9952-ES	9935-ES	1.25 in × 8 ft	31.7 mm × 2.4 m	3.6 lb (1.6 kg)
9953-ES	9936-ES	1.25 in × 10 ft	31.7 mm × 3 m	4.4 lb (2 kg)
9954-ES	-	1.25 in × 12 ft	31.7 mm × 3.6 m	5.1 lb (2.3 kg)
9955-ES	9938-ES	1.25 in × 14 ft	31.7 mm × 4.3 m	5.9 lb (2.7 kg)
9956-ES	-	1.5 in × 8 ft	38.1 mm × 2.4 m	5 lb (2.3 kg)
9957-ES	9940-ES	1.5 in × 10 ft	38.1 mm × 3 m	6 lb (2.7 kg)
9958-ES	-	1.5 in × 12 ft	38.1 mm × 3.6 m	7 lb (3.2 kg)
9959-ES	9942-ES	1.5 in × 14 ft	38.1 mm × 4.3 m	8.1 lb (3.7 kg)
9960-ES	9943-ES	1.5 in × 16 ft	38.1 mm × 4.9 m	9.1 lb (4.1 kg)
-	9944-ES	1.5 in × 18 ft	38.1 mm × 5.5 m	10.2 lb (4.6 kg)
9962-ES	-	1.5 in × 20 ft	38.1 mm × 6 m	11.2 lb (5.1 kg)

THREE SECTION

Item #	OAL Length		Top		Bottom		Weight
	ft	m	in × ft	mm × m	in × ft	mm × m	lb (kg)
4034-ES	20 ft	2 m	1.25 in × 8 ft	31.7 mm × 2.4 m	1.5 in × 6 ft	38.1 mm × 1.8 m	11.1 lb (5 kg)



Standard Prong (ST)



Heavy Duty Prong (HD)



Fiberglass Hot Switch Stick



UNIVERSAL SWITCH STICKS & ACCESSORIES

DOUBLE ENDED & TIE HEADS

SPLICE GUARDS

Splice Guards reduce the damage to the end of spliced sticks when working with only the top sections.

These foam filled FRP Hot Sticks are manufactured using a pultrusion process that results in a product with extremely high electrical and mechanical qualities.

DOUBLE ENDED UNIVERSAL

Item #	Description	Dimensions: Dia. × Length		Weight each
		in × ft	mm × m	lb (kg)
4230-ES	Stick-tie w/univ both ends 72	1.25 in × 6 ft	31.7 mm × 1.8 m	3.3 lb (1.5 kg)



Double Ended Universal Switch Stick